



# The Proven Mixproof Range

## SMP-BC Mixproof Valve

### Concept

SMP-BC is a sanitary pneumatic seat valve, designed for safety and leak detection when two different products flow through only one valve. The valve is often used as a part in CIP return lines or other systems not experiencing pressure spikes offering leakage detection for greater safety.

### Working principle

SMP-BC is remote-controlled by means of compressed air. The valve is a normally closed (NC) valve. The valve is fitted with two small pneumatic normally open (NO) valves, a detecting valve and a CIP-valve. The valve plug (the upper plug in a change-over valve) has two seals, forming a leakage chamber under atmospheric pressure between them. Leaking product flows into the leakage chamber and is discharged through the detecting valve. SMP-BC can be cleaned by CIP by supplying compressed air to the actuator (see fig. 1). During cleaning of the valve, flow pattern against the closing direction of the valve plug makes SMP-BC insensitive to water hammer.




### TECHNICAL DATA

Max. product pressure (depending on valve specifications): . . . . . 1000 kPa (10 bar).  
 Min. product pressure: . . . . . Full vacuum.  
 Temperature range: . . . . . -10°C to +140°C (EPDM).  
 Air pressure: . . . . . 500 to 800 kPa (5 to 8 bar).

### PHYSICAL DATA

Product wetted steel parts: . . . . . 1.4401 (316L).  
 External surface finish . . . Semi-bright (blasted)  
 Internal surface finish . . . Bright (polished), Ra < 1.6 µm  
 Other steel parts: . . . . . 1.4301 (304).  
 Product wetted seals: . . . EPDM.  
 Other seals: . . . . . NBR

### Valve body combination



**Type 20 and 30 body versions are on request available in following configurations:**

- Tee welded on lower port in 0 or 90 deg. version
- Bend welded on lower port in 0, 90, 180 or 270 deg. version

**The three body version is on request available in following configurations:**

- Type 121, 122, 211, 212, 221 & 222

### Standard design

SMP-BC is available in two versions, as a shut-off valve with one valve body or as a change-over valve with three valve bodies (sizes DN125-150 only as shut-off valve).

The valve bodies and the external actuator are clamped together. SMP-BC is fitted with one detecting valve and one CIP-valve. The seals and the lip seal can be serviced after removing the actuator.

It is recommended, due to the valve size and weight, to use supporting equipment, handling and installing the valve. Guidelines are given in the instruction manual (IM70771). Alfa Laval is not able to supply the recommended supporting equipment.

### Options


- A. Male parts or clamp liners in accordance with required standard.
- B. Control and Indication: IndiTop, ThinkTop or ThinkTop Basic.
- C. Actuator with stronger spring.
- D. Larger actuator for valve sizes 38-51 mm/DN40-50.
- E. CIP installation kits.
- F. Other valve body combinations.
- G. Surface roughness, product wetted parts:  $Ra \leq 0.8 \mu m$ .
- H. Product wetted seals of NBR or FPM.
- I. Service tools for actuator.
- J. Tool for plug seals (Necessary for changing the seals).

### Note!


For further details, see also instruction IM 70771.

Air consumption (litres free air) for one stroke				
Size	38-51 mm DN 40-50	63.5-101.6 mm DN 65-100	DN 125-150	DN 125-150
Stop valve	0.2 x air pressure (bar)	0.7 x air pressure (bar)	1.5 x air pressure (bar)	2.2 x air pressure (bar)
Actuator function	NO and NC	NO and NC	NC	NO
Stop valve			3.6 x air pressure (bar)	2.9 x air pressure (bar)
Actuator function			NC (Support air for closing)	NO (Support air for opening)
Change-over valve	0.2 x air pressure (bar)	0.7 x air pressure (bar)		
Actuator function	NO and NC	NO and NC		


### Operation/cleaning



a. Closed shut-off valve:  
Cleaning of the leakage chamber.






b. Open shut-off valve  
a. Cleaning of the valve body and the leakage chamber.




c. Closed change-over valve  
a. Cleaning of the upper valve body.

## Pressure drop/capacity diagrams

### Shut-off valve:







### Leakage chamber, pressure drop and flow velocity.



- 1) CIP/detecting valve  $\varnothing 27$
- 2) CIP/detecting valve  $\varnothing 32$


### Change-over valve:



**Note!** For the diagrams the following applies:  
 Medium: Water (20°C).  
 Measurement: In accordance with VDI 2173.


**Max-pressure difference/support air pressure diagrams**

Upper plug max. product pressure without leakage, as a function of support air.




Ø89 Actuator: A                      Ø133 Actuator: D  
 Ø89 Actuator with extra B        Ø133 Actuator with extra E  
 strong spring:                      strong spring:

Ø199 Actuator C  
 Upper plug max. product pressure against which the valve can open, as a function of air pressure.



Ø89 Actuator: A                      Ø133 Actuator: D  
 Ø89 Actuator with extra B        Ø133 Actuator with extra E  
 strong spring:                      strong spring:


Lower plug (change over). Max. Product pressure without leakage, as a function of air pressure.



Ø89 Actuator: A                      Ø133 Actuator: D  
 Ø89 Actuator with extra B        Ø133 Actuator with extra E  
 strong spring:                      strong spring:


**Note!** If actuator is supported by air on spring side: max allowable pressure is 300 kPa (3 bar)

Upper plug max. product pressure against which the valve can open, as a function of air pressure.



Ø89 Actuator: A                      Ø133 Actuator: D  
 Ø89 Actuator with extra B        Ø133 Actuator with extra E  
 strong spring:                      strong spring:


Lower plug (change over). Max. Product pressure without leakage, as a function of air pressure.



Ø89 Actuator: A                      Ø133 Actuator: D  
 Ø89 Actuator with extra B        Ø133 Actuator with extra E  
 strong spring:                      strong spring:


**Max-pressure difference/support air pressure diagrams**

Lower plug (change over) max. product pressure against which the valve can open by support air and spring.




A: — B: - - - D: - - - E: - - -  
 Ø89 Actuator: A Ø133 Actuator: D  
 Ø89 Actuator with extra B Ø133 Actuator with extra E  
 strong spring: strong spring:

Lower plug (change over) max. product pressure against which the valve can open by support air and spring.




D: - - - E: - - -  
 Ø133 Actuator: D  
 Ø133 Actuator with extra E  
 strong spring:

CIP/detecting valves. Max. Product pressure without leakage, as a function of air pressure.




1 CIP/detecting valve Ø27 2 CIP/detecting valve Ø32

Max. CIP pressure in leakage chamber without leakage to product area, as a function of product pressure.



I: — K: - - - H: — F: - - - G: - - -  
 Ø89 Actuator: I Ø133 Actuator: F  
 Ø89 Actuator with extra K Ø133 Actuator with extra G  
 strong spring: strong spring:  
 Ø199 Actuator: H

## Dimensions



## Dimensions (mm)

Size	38	51	63.5	76.1	101.6	40	50	65	80	100	125	150
	mm	mm	mm	mm	mm	DN	DN	DN	DN	DN	DN	DN
A <sub>1</sub>	345	355	433	455	527	343	354	430	456	526	535	584
A <sub>2</sub>	370	380	458	487	559	368	379	455	488	558	580	629
A <sub>3</sub>	485.8	505.8	616.2	651.1	751.8	485	506	616	667	752		
A <sub>4</sub>	510.8	530.8	648.2	683.1	783.8	510	531	641	699	784		
C	90	102	124	129	157	90	102	124	134	157		
C <sub>1</sub>	80	84	108	115	150	80	84	108	120.5	150		
OD	38.1	50.8	63.5	76.1	101.6	41	53	70	85	104	129	154
ID	34.9	47.6	60.3	72.1	97.6	38	50	66	81	100	125	150
t	1.6	1.6	1.6	2.0	2.0	1.5	1.5	2.0	2.0	2.0	2.0	2.0
E	49.5	61.5	82.3	87.3	133.5	49.5	61.5	82.3	87.3	133.5	150	150
E <sub>1</sub>	20.5	26.8	33.2	39.1	51.8	22	28	36	43.5	53		
F	25	25	32	32	32	25	25	32	32	32	49	49
G	27	33.3	39.7	45.6	58.3	28.5	34.5	42.5	50	59.5	72	84.5
H	89	89	133	133	133	89	89	133	133	133	199	199
J	46.7	46.7	57	66.6	84.3	46.7	46.7	57	66.6	84.3	99.5	99.5
K	63	63	63	63	63	63	63	63	63	63	58.5	58.5
M/ISO clamp	21	21	21	21	21							
M/ISO male	21	21	21	21	21							
M/DIN male						22	23	25	25	30	46	50
M/SMS male	20	20	24	24	35							
M/BS male	22	22	22	22	27							
Weight (kg)												
Stop valve	6.0	6.3	12.8	13.3	16.6	6.0	6.3	12.8	14.0	16.6	43.4	44.5
Weight (kg)												
Change-over valve	7.7	8.1	15.0	17.0	23.0	7.7	8.1	15.0	18.0	23.0		

### Air Connections Compressed air:

R 1/8" (BSP), internal thread.

### CIP connection:

R 3/8" (BSP), external thread.

### Leakage connection:

R 3/8" (BSP), external thread.

### Caution, opening/closing time:

Opening/closing time will be affected by the following:

- The air supply (air pressure).
- The length and dimensions of the air hoses.
- Number of valves connected to the same air hose.
- Use of single solenoid valve for serial connected air actuator functions.
- Product pressure.

Alfa Laval reserves the right to change specifications without prior notification. ALFA LAVAL is a trademark registered and owned by Alfa Laval Corporate AB.

ESE00281EN 1201

© Alfa Laval

---

**How to contact Alfa Laval**

Contact details for all countries are continually updated on our website. Please visit [www.alfalaval.com](http://www.alfalaval.com) to access the information direct.