



Simply Unique Single Seat

Unique SSV DN125 and DN150

Concept

Unique Single Seat DN125 and DN150 Valves are pneumatic seat valves in a sanitary and modular design giving a wide field of application, e.g. as a stop valve with two (2) or three (3) ports or as change-over valve with three (3) to five (5) ports

Working principle

The valve is remote-controlled by means of compressed air. It has few and simple moveable parts which results in a very reliable valve and low maintenance cost.

Standard Design

The Unique Single Seat DN125 and DN150 Valves come in a one or two body configuration. The actuator is connected to the valve body by means of clamp rings. To facilitate installation the valve is only partly assembled when delivered. The valve has welding ends as standard and is available with fittings as option. It is recommended, due to the valve size and weight, to use supporting equipment, handling and installing the valve. Guidelines are given in the instruction manual (IM70007). Alfa Laval is not able to supply the recommended supporting equipment.



TECHNICAL DATA


Temperature

Temperature range, standard lip seal: . . -10°C to +100°C (EPDM)
 Temperature range, special lip seal: . . -10°C to +140°C (EPDM)

Pressure

Max. product pressure: 1000 kPa (10 bar)
 Min. product pressure: Full vacuum
 Air pressure, actuator
 - Sizes DN125-150 600 to 800 kPa (6 to 8 bar)

Valve Body Combinations



Actuator function

- Pneumatic downward movement, spring return (NO-lower seat)
- Pneumatic upward movement, spring return (NC-lower seat)

PHYSICAL DATA

Materials

Product wetted steel parts: 1.4401 (316L)
 Other steel parts: 1.4301 (304)
 Plug stem sizes DN125-150 1.4401 (316L)
 Product wetted seals EPDM
 Other seals NBR


Options

- A. Male parts in accordance with required standard.
- B. Control and Indication (IndiTop, ThinkTop or ThinkTop Basic).
- C. Surface roughness, product wetted parts: $Ra \leq 0.8 \mu m$.
- D. Product wetted seals of NBR or FPM.
- E. Service tools for actuator.
- F. Plug seals NBR/FPM.


The actuator comes with a 5 years warranty

Dimensions (mm)

Nominal size	DIN DN			
	125		150	
	NC	NO	NC	NO
A ₁	571	573	584	586
A ₂	614	618	627	631
A ₃	740	737	777	775
A ₄	781	778	818	816
C	167	167	192	192
OD	129	129	154	154
ID	125	125	150	150
t	2.0	2.0	2.0	2.0
E ₁	150	150	150	150
E ₂	150	150	150	150
F ₁	43	45	43	45
F ₂	41	41	41	41
H	199	199	199	199
M/DIN male	46	46	50	50
Weight (kg) - Shut-off valve	40.3	40.3	40.9	40.9
Weight (kg) - Change-over valve	50	50	51.3	51.3



a. Shut-off .



b. Change-over valve.

Fig 2. Dimensions.

Actuator function

Size	Air consumption (litres free air) for one stroke	
	DN 125-150	DN 125-150
Shut-off / Change-over valve Actuator function	1.5 x Air pressure (bar) NC	2.2 x Air pressure (bar) NO
Shut-off / Change-over valve Actuator function	3.6 x Air pressure (bar) NC (Support air for closing)	2.9 x Air pressure (bar) NO (Support air for opening)

Please note!

Opening/closing time will be effected by the following:


- The air supply (air pressure).
- The length and dimensions of the air hoses.
- Number of valves connected to the same air hose.
- Use of single solenoid valve for serial connected air actuator functions.
- Product pressure.

Air Connections Compressed air:


R 1/8" (BSP), internal thread.

Pressure drop/capacity diagrams


Shut-off






Shut-off



Change-over valve



Change-over valve



NOTE!

For the diagrams the following applies:

Medium: Water (20°C).

Measurement: In accordance with VDI 2173

Pressure drop can also be calculated in CAS

Pressure drop can also be calculated with the following formula:

$$Q = K_v \times \sqrt{\Delta p}$$

Where

Q = Flow in m³/h.

K_v = m³/h at a pressure drop of 1 bar (see table above).

Δ p = Pressure drop in bar over the valve.

How to calculate the pressure drop for an ISO 2.5" shut-off valve if

the flow is 40 m³/h

2.5" shut-off valve, where K_v = 111 (See table above).


$$Q = K_v \times \sqrt{\Delta p}$$

$$40 = 111 \times \sqrt{\Delta p}$$

$$\Delta p = \left(\frac{40}{111}\right)^2 = 0.13 \text{ bar}$$

(This is approx. the same pressure drop by reading the y-axis above)

Pressure data for Unique Single Seat Valve DN125 and DN150



Actuator type / function

- 10. Pneumatic downward movement, spring return (NO-lower seat)
- 20. Pneumatic upward movement, spring return (NC-lower seat)

Table 1: Stop and change-over valves

Max. pressure without leakage at the valve seat

Actuator / Valve body combination and direction of pressure	Air pressure (bar)	Plug position	Valve Size	
			Type	DN 125-150
1		NO		5.2
2	5	NO	DIN	8.7
	6	NO	DIN	4.4
3	5	NC		8.1*
	6	NC		3.7
4		NC	DIN	5.2

* = Values are valid for 8 bar air pressure

† = Actual product pressure

Table 2: Stop and change-over valves

The table shows the approx. static pressure (P) in bar against which the valve can open

Actuator / Valve body combination and direction of pressure	Air pressure (bar)	Actuator type/ function	Type	DN 125-150
5		60 (NO)	DIN	8.8
6	6	10 (NO)		8.1
	6	60 (NO)		min. 10**
7	6	70 (NC)	DIN	7.8
8		20 (NC)		8.9

Alfa Laval reserves the right to change specifications without prior notification. ALFA LAVAL is a trademark registered and owned by Alfa Laval Corporate AB.

ESE00250EN 1201

© Alfa Laval

How to contact Alfa Laval

Contact details for all countries are continually updated on our website. Please visit www.alfalaval.com to access the information direct.